

KEEP THIS MANUAL FOR FUTURE REFERENCE

TYPE		WALL MOUNTED/SINGLE SPLIT/HEAT PUMP			
MODEL	OUTDOOR UNIT	AOYG30LMTA		AOYG36LMTA	
	INDOOR UNIT	ASYG30LMTA		ASYG36LMTA	
POWER SOURCE		1φ 230 V ~ 50 Hz			
		COOLING	HEATING	COOLING	HEATING
OUTDOOR TEMPERATURE	[°C]	35	7	35	7
CAPACITY	[kW]	8.0	8.8	9.4	10.1
POWER INPUT	[kW]	2.33	2.41	3.16	2.96
CURRENT	[A]	10.2	10.5	13.9	13.0
MAX. CURRENT	[A]	14.5	14.5	19.0	19.0
ENERGY EFFICIENCY RATIO/ COEFFICIENT OF PERFORMANCE	[kW/kW]	3.43	3.65	2.97	3.41
SOUND POWER LEVEL	OUTDOOR UNIT [dB(A)]	67	68	68	70
	INDOOR UNIT [dB(A)]	65	65	65	65
DIMENSION (H×W×D)	OUTDOOR UNIT [mm]	830 × 900 × 330			
	INDOOR UNIT [mm]	340 × 1150 × 280			
WEIGHT	OUTDOOR UNIT [kg]	61			
	INDOOR UNIT [kg]	18			
REFRIGERANT/GLOBAL WARMING POTENTIAL		R410A/1975			
REFRIGERANT CHARGE [kg]		2.1			
ENERGY EFFICIENCY CLASS		A**	A*	A*	A*
P <sub>design</sub>	[kW]	8.0 (35 °C)	6.5 (-10 °C)	9.4 (35 °C)	7.1 (-10 °C)
SEASONAL ENERGY EFFICIENCY RATIO/ SEASONAL COEFFICIENT OF PERFORMANCE		6.35	4.15	5.73	4.19
ANNUAL ENERGY CONSUMPTION (Q <sub>CE</sub> )(Q <sub>HE</sub> )	[kWh/a]	441	2193	575	2373
BACKUP HEATER CAPACITY/ DECLARED CAPACITY [kW]		—	0.75/5.75	—	0.86/6.24

- For more information, visit our web site at: <http://www.fujitsu-general.de/>
- For spare parts inquiry, consult the store that you purchased the product.

#### NOTES:

- Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [1975]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [1975] times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.
- Energy consumption “Q<sub>CE</sub>” kWh per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.
- Energy consumption “Q<sub>HE</sub>” kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.
- Sound pressure level : less than 70 dB(A) by according to IEC 704-1.

OPERATING RANGE		INDOOR	OUTDOOR
COOLING/DRY	[°C]	18 to 32	-15 to 46
HEATING	[°C]	16 to 30	-15 to 24
HUMIDITY	[%]	80 or less	—

- If the air conditioner is operated under higher temperature conditions than those listed, the built-in protection circuit may operate to prevent internal circuit damage. Also, during cooling and dry modes, if the unit is used under conditions of lower temperatures than those listed above, the heat-exchanger may freeze, leading to water leakage and other damage.
- If the unit is used for long periods under high-humidity conditions, condensation may form on the surface of the indoor unit, and drip onto the floor or other objects underneath.